

**Listing of Claims:**

Claim 1. (Currently Amended): An apparatus for displaying screen saver views managed by a screen saver program and generated by a computer application operating in a screen saver mode, the computer application being an independent program from the screen saver program, the apparatus comprising:

~~a processor coupled to the storage medium that performs the following steps:~~

(a) ~~monitoring the apparatus for detecting inputs from a command entry device;~~

(b) ~~determining whether a timeout period of inactivity from the inputs has been exceeded;~~

(c) ~~in response to step (b), starting the screen saver program; and~~

(d) ~~executing the application in the screen saver mode based on instructions from the screen saver program, the application being a program independent from the screen saver program that is fully functional in a full application mode and that is less than fully functional in a screen saver mode, the application creating an image for presentation on a display screen in the screen saver mode.~~

a storage medium;

a carousel stored in the storage medium; said carousel including plural application handles; and

a processor coupled to the storage medium, said processor configured to monitor the apparatus for detecting inputs from a command entry device, to determine whether a timeout period of activity from the inputs has been exceeded, to start a screen saver program when said timeout period of activity has been exceeded, and to execute an application via one of said handles, the application being an independent program from said screen saver program and operable in a full application mode and a screen saver mode, the application being fully functional in said full application mode and less than fully functional in said screen saver mode, the application creating an image for presentation on a display screen in said screen saver mode.

Claim 2. (Original): The apparatus of claim 1, wherein the apparatus comprises a wireless communication device.

Claim 3. (Canceled)

Claim 4. (Currently Amended): The apparatus of claim 3 1, wherein the carousel comprises a database stored in the storage medium containing the application handle and rules for selecting the application handle.

Claim 5. (Original): The apparatus of claim 4, wherein the rules are definable by a user of the apparatus.

Claim 6. (Original): The apparatus of claim 4, wherein the rules comprise default rules.

Claim 7. (Original): The apparatus of claim 4, wherein the database further contains application execution parameters associated with the handle, wherein the application is executed in the screen saver mode according to the parameters associated with the handle selected for executing the application.

Claim 8. (Previously Presented): The apparatus of claim 7, wherein the application additionally has another handle comprising different execution parameters.

Claim 9. (Currently Amended): The apparatus of claim 1, wherein the apparatus is in communication configured to communicate with a network and displays current information generated by the application operating in the screen saver mode based on data received from the network.

Claim 10. (Previously Presented): The apparatus of claim 9, wherein images generated by the application for presentation on the display screen in the screen saver mode are continually updated in response to data received from the network.

Claim 11. (Currently Amended): The apparatus of claim 1, wherein the processor further ~~performs the step of (e) executing~~ is configured to execute at least one additional application in a

corresponding screen saver mode, the at least one additional application being a program that is fully functional in a corresponding full application mode and that is less than fully functional in a corresponding screen saver mode, the at least one additional application creating images for presentation on the display screen in the corresponding screen saver mode.

Claim 12. (Canceled)

Claim 13. (Currently Amended): The apparatus of claim 42 11, wherein the order comprises rules for scheduling the execution of applications in their respective screen saver modes.

Claim 14. (Currently Amended): A wireless communication device, comprising:

a receiver;

a memory storing data;

a display screen;

at least one application stored in the memory having at least one handle executing the at least one application in a screen saver mode when the at least one handle is selected, the at least one handle being contained in a carousel, the at least one application creating images for presentation on the display screen in the screen saver mode, the at least one application being fully functional in a full application mode and less than fully functional in a screen saver mode; and

a screen saver program stored in the memory that, during operation of the screen saver program, selects the at least one application handle, the screen saver program being an independent program from the at least one application.

Claim 15. (Canceled):

Claim 16. (Currently Amended): The wireless communication device of claim 45 14, wherein the carousel comprises a database stored in the memory containing the at least one application handle and rules for selecting the at least one application handle.

Claim 17. (Original): The wireless communication device of claim 16, wherein the rules are definable by a user of the communication device.

Claim 18. (Original): The wireless communication device of claim 16, wherein the rules comprise default rules.

Claim 19. (Original): The wireless communication device of claim 16, wherein the database further contains application execution parameters associated with the at least one handle, wherein the at least one application is executed in a screen saver mode according to the parameters associated with the at least one handle selected for executing the at least one application.

Claim 20. (Previously Presented): The wireless communication device of claim 19, wherein the at least one application additionally has another handle associated with the at least one application, the another handle comprising different execution parameters.

Claim 21. (Original): The wireless communication device of claim 14, wherein the at least one application comprises a network application creating images responsive to data received during operation in the screen saver mode.

Claim 22. (Original): The wireless communication device of claim 21, wherein one of the parameters associated with the network application is a uniform resource locator (URL).

Claim 23. (Previously Presented): The wireless communication device of claim 14, wherein the at least one application is written in a JAVA programming language.

Claim 24. (Currently Amended): A method comprising:  
in a device comprising a display screen, a storage medium, a screen saver computer  
program stored in the storage medium, a screen saver carousel stored in the storage medium, and  
an application stored in the storage medium, the application being a program that is independent

from the screen saver program, said carousel including plural application handles, starting the screen saver program in response to exceeding a timeout period of inactivity; and

selecting an application handle via the screen saver program to execute the application associated with the selected handle in a screen saver mode, the application being fully functional in a full application mode and less than fully functional in said screen saver mode.

~~A method of creating screen saver displays on a display device, the device having a display screen, a storage medium, a screen saver computer program stored in the storage medium, a screen saver carousel stored in the storage medium, and an application stored in the storage medium that is fully functional in a full application mode and less than fully functional in a screen saver mode, the application being a program that is independent from the screen saver program, the method comprising the steps of:~~

~~adding an application handle to execute the application in the screen saver mode to the screen saver carousel;~~

~~starting the screen saver program in response to exceeding a timeout period of inactivity; and~~

~~selecting the application handle via the screen saver program to execute the application in the screen saver mode.~~

Claim 25. (Currently Amended): The method of claim 24, further comprising the following steps:

installing the application on the display device; and

selecting an option for the application to operate in the screen saver mode.

Claim 26. (Currently Amended): The method of claim 24, wherein the application is pre-installed on the device, further comprising the following steps:

executing the application in a full application mode on the display device; and

selecting an option for installing a screen saver mode for the application to operate in the screen saver mode.

Claim 27. (Currently Amended): The method of claim 24, further comprising the steps of:

monitoring the display device for a timeout signal that the application has exceeded a time period allotted for operation in the screen saver mode; and

in response to detecting the timeout signal, if another application has been configured to operate in a screen saver mode, executing another application in a screen saver mode associated with the another application.

Claim 28. (Currently Amended): The method of claim 24, further comprising the steps of:

monitoring the display device for an input signal from a command entry device; and

if a signal is received from the command entry device after the application has been executed, determining whether the executed application operating in the screen saver mode is an interactive application; and

if the executed application is an interactive program, terminating the screen saver program, and

executing the interactive program in a full application mode.

Claim 29. (Currently Amended): A computer readable medium having computer-executable instructions, ~~for performing steps comprising: that, when executed, perform a method comprising:~~

monitoring activity on a device having a display screen;

determining whether a timeout period of inactivity on the device has been exceeded;

starting a screen saver program;

~~evaluating whether a screen saver carousel contains application handles, each of the application handles executing a respective application in a screen saver mode when selected by the screen saver program, the application being an independent program from the screen saver program and being a program that is fully functional in a full application mode and that is less than fully functional in a screen saver mode; and~~

~~if the carousel contains at least one application handle, and if the timeout period has been exceeded, selecting the at least one application handle to execute the respective application.~~

from a screen saver carousel that contains plural application handles, selecting an application handle to execute the application if the timeout period has exceeded application, each of the application handles executing an application in a screen saver mode when selected by the

screen saver program, the application being an independent program from the screen saver program and being a program that is fully functional in a full application mode and that is less than fully functional in a screen saver mode.

Claim 30. (Original): The computer readable medium of claim 29, wherein the activity being monitored is the detection of input signals from a command entry device in communication with the device, the steps further comprising:

if a signal is not received from the command entry device, if a timeout period for operation of the respective application is exceeded, and if the carousel contains more than one handle,  
selecting a different handle to execute another respective application associated with the different handle.

Claim 31. (Original): The computer readable medium of claim 30, wherein the respective application associated with the at least one handle and the respective application associated with the different handle are the same application configured for operation in different screen saver modes depending on the handle selected.

Claim 32. (Original): The computer readable medium of claim 30, wherein the respective application associated with the at least one handle and the respective application associated with the different handle are different applications.

Claim 33. (Original): The computer readable medium of claim 29, wherein the activity being monitored is the reception of input signals from a command entry device in communication with the device, the steps further comprising:

if a signal is received from the command entry device after the respective application is executed, determining whether the respective application currently operating in the screen saver mode is an interactive application; and

if the respective application is an interactive program,  
terminating the screen saver program, and  
executing the respective interactive program in a full application mode.

Claim 34. (Currently Amended): A ~~portable~~ device comprising:

a display screen;

a memory;

a command entry device;

a computer application stored in the memory, the application having at least one handle executing the application in a screen saver mode when the at least one handle is selected, the application being a program that is fully functional in a full application mode and is less than fully functional in a screen saver mode, the application creating images for presentation on the display screen in the screen saver mode;

a different computer application stored in the memory having at least one different handle executing the different application in a different screen saver mode when the at least one different handle is selected;

rules stored within the memory for determining the scheduling for selecting the at least one handle;

parameters stored within the memory associated with the at least one handle for controlling operational aspects of the application;

a screen saver program stored in the memory ~~selecting~~ and configured to select the at least one application handle during operation of the screen saver program according to the rules, the screen saver program being a program that is independent from the computer applications; and

a processor coupled to the memory that ~~performs the steps of~~ is configured to perform:

monitoring ~~the device~~ for ~~detecting~~ inputs from the command entry device;

determining whether a timeout period of inactivity from the inputs has been exceeded; in accordance with instructions from the screen saver program, selecting the at least one application handle stored in the carousel;

if a signal is not detected from the command entry device since the period of inactivity was exceeded, and if a timeout period for operation of the application is exceeded, selecting the different handle to execute the different application associated with the different handle in its respective different screen saver mode;

if a signal is detected from the command entry device since the period of inactivity was exceeded, determining whether the executed application operating in the screen saver mode is an interactive application; and

if the executed application is interactive, terminating the screen saver program, and



executing the executed interactive program in a full application mode.

Claim 35. (Currently Amended): The apparatus of claim 1, wherein, ~~prior to performing step (d), the processor performs further steps comprising:~~

(f) ~~executing~~ the processor is configured to execute the application in a full application mode in response to user selection of the application; and

(g) ~~adding~~ the processor is configured to add an application handle to the carousel in response to user selection of a screen saver mode option presented by the application while in full application mode.

Claim 36. (Previously Presented): The wireless communication device of claim 14, wherein the at least one application includes one or more screen saver mode options selectable by a user when operating the at least one application in a full application mode, the screen saver mode options including a level of functionality that is less than the functionality of the full application mode.

Claim 37. (Currently Amended): The method of claim 24 wherein, ~~prior to the steps of adding, starting and selecting,~~ the method further comprises:

executing the application in a full application mode in response to user selection of the application; and

adding an application handle to the screen saver carousel in response to user selection of a screen saver mode option presented by the application while in full application mode.

Claim 38. (New) An apparatus comprising:

a processor programmed to generate a user interface on a display, said processor being configured to generate a display of an application running in a full application mode and a display of said application running in a screen saver mode, the application being fully functional in a full application mode and less than fully functional in a screen saver mode, said processor being configured to display a configuration tool that is configured to permit a user to modify rules and parameters for said application, said apparatus including a storage medium and a carousel stored in the storage medium, the carousel including plural application handles, said processor being

configured to start a screen saver program when a period of timeout activity has been exceeded and to execute said application via one of said handles, the application being an independent program from said screen saver program.

Claim 39. (New) An apparatus according to claim 38, said configuration tool being configured to permit a user to add or delete application handles from said carousel.